

Folder-gluer belts: portfolio and applications

Machine speed [m/min] ↑ 600 300	Mainly carton	<p>Thermoplastic belts with PET fabric and NBR cover: Habasit Flexfold® CT-18/30E Habasit Flexfold® CT-18/40E Color: gray/gray</p>	<p>For heavy load and/or moderate speed PA-F/G belts with NBR cover: XVT-2236 (S-18/60) XVT-2237 (S-10/30) XVT-2238 (S-10/40) Color: green/yellow</p>
	Mainly corrugated	<p>For heavy load and tough conditions Thermoplastic belts with 2 PA fabrics, thermoplastic foil and NBR cover: XVT-2205 (t=3 mm) XVT-2213 (t=4 mm) XVT-2226 (t=5 mm) Color: green/yellow</p> <p>Speed limit max. 300 m/min</p>	
		Adhesive-free joining (Flexproof)	Joining by gluing (Thermofix)



Faltschachtelriemen Produktpalette und Anwendungen

Maschinengeschwindigkeit [m/min]	↑ 600 Vorwiegend Karton	Thermoplastische Bänder mit PET-Gewebe und NBR-Beschichtung: Habasit Flexfold® CT-18/30E Habasit Flexfold® CT-18/40E Farbe: grau/grau	Für hohe Kräfte und/oder mäßige Geschwindigkeit PA-Bänder mit NBR-Beschichtung: XVT-2236 (S-18/60) XVT-2237 (S-10/30) XVT-2238 (S-10/40) Farbe: grün/gelb
	300 Vorwiegend Wellpappe	Für hohe Kräfte und anspruchsvolle Betriebsbedingungen Thermoplastische Bänder mit 2 PA Geweben, thermoplastischer Folie und NBR-Beschichtung: XVT-2205 (t=3 mm) XVT-2213 (t=4 mm) XVT-2226 (t=5 mm) Farbe: grün/gelb Geschwindigkeitsbegrenzung max. 300 m/min	
		Klebstofffreie Endverbindung (Flexproof)	Geklebte Endverbindung (Thermofix)

